


100W Single Output Series



- AC input range selected by switch
- High reliability
- Protections: over current/ over voltage/ short circuit
- 2 years warranty
- N610 199 x 98 x 39(mm)

AC input voltage range	85~132/ 170~264VAC selected by switch
Input frequency	47~63Hz
Inrush current	cold start, 20A/115V, 40A/230V
Input leakage current	< 0.7mA/ 230VAC
Line regulation (full load)	$\leq \pm 0.5\%$
Output voltage adjust range	$\pm 10\%$
Output over current protection	110~130%
Output over voltage protection	115~150%
Withstand voltage	I/P -O/P: 3.0KVAC/1min I/P -F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min
Rise, Hold up time	50ms, 20ms@full load (typical)
Operating temp. & humidity	-10°C~+50°C, 20%~93%RH (non condensing)
Storage temp. & humidity	-20°C~+85°C, 20%~95%RH (non condensing)
Safety standards	GB4943, UL60950, EN60950
EMC standards	GB9254, EN55022 classB, EN55024 EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11
Cooling method	convection

Model	DC Output		Load regul.	R&N	Efficiency
NO100W-SF-5	5V	20.0A	0.5%	100mV	77%
NO100W-SF-7.5	7.5V	13.5A	0.5%	100mV	78%
NO100W-SF-12	12V	8.5A	0.5%	100mV	82%
NO100W-SF-13.8	13.8V	7.5A	0.5%	100mV	82%
NO100W-SF-15	15V	6.7A	0.5%	100mV	82%
NO100W-SF-24	24V	4.5A	0.5%	100mV	83%
NO100W-SF-48	48V	2.2A	0.5%	150mV	84%

* 3~48VDC output all available.

Drawing

