


150W Single Output Mini-size Series



- Compact size, high reliability
- AC input range selected by switch
- 100% full load burn-in test
- Protections: over current/ over voltage/ short circuit
- 2 years warranty
- N610 199 x 98 x 39(mm)

AC input voltage range	85~132/ 170~264VAC selected by switch
Input frequency	47~63Hz
Inrush current	cold start, 20A/115V, 40A/230V
Input leakage current	< 0.7mA/ 230VAC
Line regulation (full load)	≤ ± 0.5%
Output voltage adjust range	± 10%
Output over current protection	110~130%
Output over voltage protection	115~150%
Withstand voltage	I/P -O/P: 3.0KVAC/1min I/P -F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min
Rise time	50ms@full load (typical)
Hold up time	20ms@full load (typical)
Operating temp. & humidity	-10℃~+50℃, 20%~93%RH (non condensing)
Storage temp. & humidity	-20℃~+85℃, 20%~95%RH (non condensing)
Safety standards	meet GB4943, UL60950, EN60950
EMC standards	meet GB9254, EN55022 classB EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11
Cooling method	convection

Model	DC Output		Load regul.	R&N	Efficiency
NO150W-SMF-5	5V	25.0A	0.5%	100mV	78%
NO150W-SMF-12	12V	12.5A	0.5%	120mV	82%
NO150W-SMF-15	15V	10.0A	0.5%	120mV	83%
NO150W-SMF-24	24V	6.3A	0.5%	150mV	85%
NO150W-SMF-48	48V	3.1A	0.5%	150mV	87%

* 3~48VDC output all available.

Drawing

