240W Single Output Series

- AC input range selected by switch
- High reliability
- Protections: over current/ over voltage/ short circuit
- 2 years warranty
- N615UL 199 x 110 x 50(mm)

AC input voltage range	85~132/ 170~264VAC selected by switch
Input frequency	47~63Hz
Inrush current	cold start, 20A/115V, 40A/230V
Input leakage current	＜0.7mA/ 230VAC
Line regulation (full load)	≤±0.5%
Output voltage adjust range	±10%
Output over current protection	110~130%
Output over voltage protection	115~150%
Withstand voltage	I/P -O/P: 3.0KVAC/1min I/P -F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min
Rise, Hold up time	50ms, 20ms@full load (typical)
Operating temp. & humidity	-10℃~+50℃, 20%~93%RH (non condensing)
Storage temp. & humidity	-20℃~+85℃, 20%~95%RH (non condensing)
Safety standards	meet GB4943, UL60950, EN60950
EMC standards	meet GB9254, EN55022 classA
Cooling method	convection

Model	DC Output		Load regul.	R&N	Efficiency
NO240W-SF-5	5V	40.0A	0.5%	100mV	80%
NO240W-SF-7.5	7.5V	30.0A	0.5%	100mV	82%
NO240W-SF-12	12V	18.0A	0.5%	100mV	83%
NO240W-SF-15	15V	15.0A	0.5%	100mV	84%
NO240W-SF-24	24V	10.0A	0.5%	120mV	85%
NO240W-SF-30	30V	8.0A	0.5%	150mV	86%
NO240W-SF-48	48V	5.0A	0.5%	150mV	87%

* 3~48VDC output all available.

Drawing