

## 350W Single Output Series



- AC input range selected by switch
- High reliability
- Built in fan speed control
- Protections: over current/ over voltage/ over temperature/ short circuit
- 2 years warranty
- N632C 215 x 115 x 50(mm)

AC input voltage range .....	85~132/ 170~264VAC selected by switch
Input frequency .....	47~63Hz
Inrush current .....	cold start, 20A/115V, 40A/230V
Input leakage current .....	< 0.7mA/ 230VAC
Line regulation (full load) .....	≤ ± 0.5%
Output voltage adjust range .....	± 10%
Output over current protection .....	110~130%
Output over voltage protection .....	115~150%
Withstand voltage .....	I/P -O/P: 3.0KVAC/1min I/P -F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min
Rise time .....	50ms@full load (typical)
Hold up time .....	20ms@full load (typical)
Operating temp. & humidity .....	-10°C~+50°C, 20%~93%RH (non condensing)
Storage temp. & humidity .....	-20°C~+85°C, 20%~95%RH (non condensing)
Safety standards .....	meet GB4943, UL60950, EN60950
EMC standards .....	meet GB9254, EN55022 classA
Cooling method .....	fan

Model	DC Output		Load regul.	R&N	Efficiency
NO350W-SF-5	5V	60.0A	0.5%	150mV	75%
NO350W-SF-7.5	7.5V	40.0A	0.5%	150mV	77%
NO350W-SF-12	12V	29.0A	0.5%	150mV	75%
NO350W-SF-13.5	13.5V	25.8A	0.5%	150mV	80%
NO350W-SF-15	15V	23.2A	0.5%	150mV	79%
NO350W-SF-24	24V	14.6A	0.5%	150mV	82%
NO350W-SF-27	27V	13.0A	0.5%	150mV	83%
NO350W-SF-48	48V	7.3A	0.5%	240mV	84%

\* 3~48VDC output all available.

## Drawing

