

800~1000W Single Output Series



- High reliability, low cost
- Built in fan speed control
- 100% full load burn-in test
- Protections: over current/ over voltage/ over temperature/ short circuit
- 1 year warranty
- N650 250 x 160 x 87(mm)

AC input voltage range	170~264VAC (210~370VDC)
Input frequency	47~63Hz
Inrush current	60A/230V
Input leakage current	< 0.7mA/ 230VAC
Line regulation (full load)	≤ ± 0.5%
Output voltage adjust range	± 10%
Output over current protection	110~130%, current limiting, auto recovery
Output over voltage protection	115~150%
Withstand voltage	I/P -O/P: 1.5KVAC/1min I/P -F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min
Rise time	50ms@full load (typical)
Hold up time	20ms@full load (typical)
Operating temp. & humidity	-10°C~+50°C, 20%~90%RH (non condensing)
Storage temp. & humidity	-20°C~+85°C, 20%~95%RH (non condensing)
Safety standards	design refer to GB4943, UL60950, EN60950
EMC standards	design refer to GB9254, EN55022 classA
Cooling method	fan

Model	DC Output		Load regul.	R&N	Efficiency
NO800W-S-24	24V	33.0A	0.5%	180mV	85%
NO800W-S-28	28V	30.0A	0.5%	180mV	85%
NO800W-S-48	48V	17.0A	0.5%	250mV	87%
NO800W-S-110	110V	7.3A	0.5%	600mV	89%
NO900W-S-30	30V	30.0A	0.5%	200mV	86%
NO1000W-S-24	24V	42.0A	0.5%	180mV	85%
NO1000W-S-28	28V	35.0A	0.5%	200mV	86%
NO1000W-S-48	48V	21.0A	0.5%	300mV	87%

* 24~110VDC output all available.

Drawing

